



CIVIL AVIATION PUBLICATION

CAP 05

ALL WEATHER OPERATIONS

INDEX

This Page Intentionally Left Blank



CAP 05

ALL WEATHER OPERATIONS

INDEX

Section	Title	Page No.
1.	Introduction	1
1.1	General	1
1.2	Applicability	1
1.3	References	1
1.4	Terminology	1
2.	Instruments and Equipment	2
2.1	General	2
2.2	Required Instruments and Equipment	2
3	Approval Process	4
3.1	Application	4
3.2	Supporting Documentation	4
3.3	Operations Evaluation Programme for Commercial Air Transport Operators (only)	6
3.3.1	General	6
3.3.2	Demonstrations	7
3.3.3	Records	9
4.	Certification	10
4.1	Approval.....	10
4.2	Certificate of Competency	10
5.	Operating Procedures	10
6.	Approval	10



This Page Intentionally Left Blank



1. INTRODUCTION

1.1 General

Air Weather Operations (AWO or AWOPS) applies to an operator who requires an ILS landing minima with a decision height lower than 200 feet and a RVR of less than 400 metres. Appropriate Low Visibility Procedures must be in force at an aerodrome, according to information received from Air Traffic Services, before commencing a Low Visibility Take-off, a Lower than Standard Category I or a Category II or III approach.

Note: Please refer to CAP 07 for additional operational approval requirements for the use of Head-up Display and Enhanced Visual Systems (HUD/EVS).

This CAP provides information on the application, required equipment, the approval process, as well as guidance on operational procedures and training. All San Marino registered aircraft planning to conduct AWO operations shall be required to obtain an approval from the CAA before the commencement of operations.

1.2 Applicability

This guidance material is intended for all operators of San Marino registered aircraft planning to conduct All Weather Operations. This CAP applies to the initial issue of AWO for LVTO, Lower than Standard CAT I and CAT II/III ILS. AWO approval will be granted only to operators of aircraft with the appropriate equipment and applying additional training, procedures and maintenance.

Note1: Applicants for Lower than Standard CAT II or CAT III should contact the CAA directly for additional guidance as these privileges are only granted to an operator which has previous documented experience with Cat II.

Note2: The process for operational approval is the same for AOC holders and General Aviation operators.

1.3 References

The following references should be used when applying for All Weather Operations;

- (a) CAR OPS 1, Subpart E (primary reference for all operators and must be reviewed before application. It can be downloaded from CAA website)
- (b) FAA Advisory Circular 120-29.

1.4 Terminology

Category II - Landing following a precision approach using an Instrument Landing System or Microwave System with a decision height of below 200 feet but not less than 100 feet. Runway visual range: not less than 300 metres.



Category IIIA - Landing following a precision approach using an Instrument Landing System with a decision height lower than 30 m (100 ft) or no decision height and a runway visual range not less than 200 m;

Category IIIB - Landing following a precision approach using an Instrument Landing System or Microwave System with a decision height lower than 50 ft, or no decision height and a runway visual range less than 200 m but not less than 75 m;

Category IIIC - Landing following a precision approach using an Instrument Landing System or Microwave System with no decision height and no runway visual range limitations.

Lower than Standard Category I Operation. A Category I Instrument Approach and Landing Operation using Category I DH, with an RVR lower than would normally be associated with the applicable DH.

Low Visibility Procedures (LVP). Procedures applied at an aerodrome for the purpose of ensuring safe operations during Category II approaches and Low Visibility Take-offs.

Note: Some States refer to LVP (as applied at an aerodrome) as All Weather Operations (AWO).

Low Visibility Take-Off (LVTO). A take-off where the Runway Visual Range (RVR) is less than 400 m.

2. INSTRUMENTS AND EQUIPMENT

2.1 General

The AFM (or supplement) should indicate that the aircraft is approved for AWO and the instruments and equipment, as fitted, would normally meet the certification requirements for AWO. The required instruments and equipment must be installed in each aircraft and;

- (a) all instruments and items of equipment required must be capable of performing as necessary for AWO operations; and
- (b) the MEL must reflect AWO procedures.

Approval is also required after each subsequent alteration to these instruments and items of equipment. The CAA requires the aircraft to be equipped in accordance with EASA CS-AWO or an equivalent standard accepted by the Authority.

2.2 Required Instruments and Equipment

- (a) Two localiser and glide slope receiving systems. Each system must provide a basic ILS display and each side of the instrument panel must have a basic ILS display. However, a single localiser antenna and a single glide slope antenna may be used.
- (b) A communications system that does not affect the operation of at least one of the ILS systems.



- (c) A marker beacon receiver that provides distinctive aural and visual indications of the outer and the middle markers.
- (d) Two gyroscopic pitch and bank indicating systems.
- (e) Two gyroscopic direction indicating systems.
- (f) Two airspeed indicators.
- (g) Two sensitive altimeters adjustable for barometric pressure, having markings at 20 foot intervals and each having a placarded correction for altimeter scale error and for the wheel height of the aircraft.
- (h) Two vertical speed indicators.
- (i) A flight control guidance system that consists of either an automatic approach coupler or a flight director system. A flight director system must display computed information as steering command in relation to an ILS localiser and, on the same instrument, either computed information as pitch command in relation to an ILS glide slope or basic ILS glide slope information. An automatic approach coupler must provide at least automatic steering in relation to an ILS localiser. The flight control guidance system may be operated from one of the receiving systems required by subparagraph (a) of this paragraph.
- (j) For Category II operations with decision heights below 150 feet either a marker beacon receiver providing aural and visual indications of the inner marker or a radio altimeter.
- (k) Warning systems for immediate detection by the pilot of system faults in items (a), (d), (e), and (i).
- (l) Dual controls.
- (m) An externally vented static pressure system with an alternate static pressure source.
- (n) A windshield wiper or equivalent means of providing adequate cockpit visibility for a safe visual transition by either pilot to touchdown and rollout.
- (o) A heat source for each airspeed system pitot tube installed or an equivalent means of preventing malfunctioning due to icing of the pitot system.
- (p) A radio altimeter must meet the performance criteria of this paragraph for original approval and after each subsequent alteration.
 - (1) It must display to the flight crew clearly and positively the wheel height of the main landing gear above the terrain.
 - (2) It must display wheel height above the terrain to an accuracy of ± 5 feet or 5 percent, whichever is greater, under the following conditions:



- (i) Pitch angles of zero to $\pm 5^\circ$ about the mean approach attitude.
 - (ii) Roll angles of zero to 20° in either direction.
 - (iii) Forward velocities from minimum approach speed up to 200 knots.
 - (iv) Sink rates from zero to 15 feet per second at altitudes from 100 to 200 feet.
- (3) Over level ground, it must track the actual altitude of the aircraft without significant lag or oscillation.
 - (4) With the aircraft at an altitude of 200 feet or less, any abrupt change in terrain representing no more than 10 percent of the aircraft's altitude must not cause the altimeter to unlock, and indicator response to such changes must not exceed 0.1 seconds and, in addition, if the system unlocks for greater changes, it must reacquire the signal in less than 1 second.
 - (5) Systems that contain a push to test feature must test the entire system (with or without an antenna) at a simulated altitude of less than 500 feet.
 - (6) The system must provide to the flight crew a positive failure warning display any time there is a loss of power or an absence of ground return signals within the designed range of operating altitudes.

3. APPROVAL PROCESS

3.1 Application

An application for Air Weather Operations approval must be submitted to the CAA for their initial review using the Form SM 05 for General Aviation operators and Form SM 05A for Commercial Air Transport operators. Any required operational supporting documentation must be included in the application as an attachment.

3.2 Supporting Documentation

An applicant from a General Aviation operator to operate on AWO must provide evidence of aircraft system capability and declare in a Declaration of Compliance (refer Form SM 05) that the aircraft has suitably approved equipment (is eligible), the pilot is suitably qualified and current with respect to the equipment and adequate procedures and checklists are in place.

An applicant from a Commercial Air Transport operator to operate on AWO must submit all supporting documentation below for approval. Training at paragraph (e) below should be observed.

The supporting documentation must be sufficient for the CAA to be able to make a determination. The relevant section of the AFM (or supplement) and documentation on modifications, STC etc. for the aircraft serial number must be included as well as proposed amendments to;



- (a) MMEL/MEL addressing AWO (requires CAA approval).
- (b) Maintenance Programme. Maintenance instructions for the on-board guidance systems must be established by the operator, in liaison with the manufacturer, and included in the operator's aeroplane maintenance programme, which must be acceptable to the Authority.

Note: The operator must include procedures for the maintenance of AWO equipment such as adherence to manufacturer's instructions, modification procedures, repair procedures, system calibration policy etc. Additional engineering procedures should include action for downgrading and upgrading such as technical log entries, corrective action, placarding, release to service procedures, monitoring reliability of AWO critical components and reporting to CAA etc.

- (c) MME if applicable
- (d) Operations Manual

All operators must ensure the following procedures and requirements are addressed. A General Aviation operator must make a declaration that the Operations Manual complies whereas a Commercial Air Transport operator must submit the Operations Manual (or amendment) to the CAA for approval. SOPs must cover applicable operator requirements such as;

- Definitions.
- Crew qualifications for AWO
- Equipment required for AWO
- MEL handling.
- Data collection
- Crew briefing
- Low Visibility Take-Off:
 - Taxiing in low visibility conditions.
 - Take-off minima and lighting.
 - Crew visual visibility assessment.
 - Crew responsibilities/handling.
 - Visual references required.
 - Approved lateral guidance system.
 - ATC calls.
 - Contingency procedures including: engine failure between V_1 and V_R ; and rejected take-off.
- Approach and landing:
 - Modes of operation.
 - Statement that autopilot/flight director must be used whenever possible.
 - AWO fuel considerations.
 - Minimum visual references for landing.
 - Approach Ban and RVR.
 - Cross-wind limits.
 - Effect of irregular pre-threshold terrain.
 - Stabilised approach criteria.



- Correct seating and eye position.
- Designation of PF and PNF and their duties.
- Use of automatic flight control system.
- Checklist handling.
- Approach briefing.
- Radio communications handling.
- Monitoring and cross-checking of instruments and radio aids.
- Cockpit call outs.
- Contingency procedures including:
 - use of equipment downgrade list;
 - failures above and below decision height;
 - ILS deviation warnings;
 - autopilot disconnect;
 - auto-throttle disconnect;
 - electrical failures;
 - engine failure;
 - failures and loss of visual references at or below decision height; and pilot incapacitation.

(e) Training

Appropriate formal AWO training at a TRTO approved for the purpose, using a simulator for the type of aircraft applied for, in respect to the following (as appropriate);

- Initial training
- Recurrent training/qualification
- Upgrade training
- Recency of experience
- Differences training
- Simultaneous training and qualification for AWO
- Ground training curriculum segment
- Surface movement control training
- Flight training curriculum segment
- Initial qualification
- Low visibility take-off qualification
- Multiple aircraft type or variant qualification (as applicable)
- Line checks
- Crew records and notification system

3.3 Operations Evaluation Programme for Commercial Air Transport Operators (only)

3.3.1 General

The CAA must evaluate, and approve where necessary, the following before operational approval;

- (a) TRTO & FSTD capability;
- (b) Training programme;



- (c) Aircraft systems;
- (d) Operating instructions (Operations Manual and MEL);
- (e) Operational procedures (FSTD and in-flight);

3.3.2 Demonstrations

Unless otherwise authorised by the CAA, the evaluation programme for each aircraft requires the demonstrations as specified in Appendix 1 to CAR OPS 1.440, as follows.

- (a) *General.* The following procedures apply to the introduction and approval of low visibility operations.
- (b) *Operational Demonstration.* The purpose of the operational demonstration is to determine or validate the use and effectiveness of the applicable aircraft flight guidance systems, training, flight crew procedures, maintenance programme, and manuals applicable to the Category II/III programme being approved.
 - (1) At least 30 approaches and landings must be accomplished in operations using the Category II/III systems installed in each aircraft type if the requested DH is 50 ft or higher. If the DH is less than 50 ft, at least 100 approaches and landings will need to be accomplished unless otherwise approved by the Authority.
 - (2) If an operator has different variants of the same type of aircraft utilising the same basic flight control and display systems, or different basic flight control and display systems on the same type of aircraft, the operator must show that the various variants have satisfactory performance, but the operator need not conduct a full operational demonstration for each variant. The Authority may also accept a reduction of the number of approach and landings based on credit given for the experience gained by another operator using the same aeroplane type or variant and procedures.
 - (3) If the number of unsuccessful approaches exceeds 5 % of the total (e.g. unsatisfactory landings, system disconnects) the evaluation programme must be extended in steps of at least 10 approaches and landings until the overall failure rate does not exceed 5 %.
- (c) *Data Collection for Operational Demonstrations.* Each applicant must develop a data collection method (e.g. a form to be used by the flight crew) to record approach and landing performance. The resulting data and a summary of the demonstration data shall be made available to the Authority for evaluation.
- (d) *Data Analysis.* Unsatisfactory approaches and/or automatic landings shall be documented and analysed.



(e) *Continuous Monitoring*

- (1) After obtaining the initial authorisation, the operations must be continuously monitored by the operator to detect any undesirable trends before they become hazardous. Flight crew reports may be used to achieve this.
- (2) The following information must be retained for a period of 12 months:
 - (i) The total number of approaches, by aeroplane type, where the airborne Category II or III equipment was utilised to make satisfactory, actual or practice, approaches to the applicable Category II or III minima; and
 - (ii) Reports of unsatisfactory approaches and/or automatic landings, by aerodrome and aeroplane registration, in the following categories:
 - (A) Airborne equipment faults;
 - (B) Ground facility difficulties;
 - (C) Missed approaches because of ATC instructions; or
 - (D) Other reasons.
- (3) An operator must establish a procedure to monitor the performance of the automatic landing system of each aeroplane.

(f) *Transitional periods*

- (1) *Operators with no previous Category II or III experience*
 - (i) An operator without previous Category II or III operational experience may be approved for Category II or IIIA operations, having gained a minimum experience of 6 months of Category I operations on the aeroplane type.
 - (ii) On completing 6 months of Category II or IIIA operations on the aeroplane type the operator may be approved for Category IIIB operations. When granting such an approval, the Authority may impose higher minima than the lowest applicable for an additional period. The increase in minima will normally only refer to RVR and/or a restriction against operations with no decision height and must be selected such that they will not require any change of the operational procedures.
- (2) *Operators with previous Category II or III experience.*

An operator with previous Category II or III experience may obtain authorisation for a reduced transition period by providing evidence of that experience as supporting documentation with the application.



- (g) *Maintenance of Category II, Category III and LVTO equipment.* Maintenance instructions for the on-board guidance systems must be established by the operator, in liaison with the manufacturer, and included in the operator's aeroplane maintenance programme which must be approved by the Authority.
- (h) Eligible Aerodromes and Runways
- (1) Each aeroplane type/on-board equipment/runway combination must be verified by the successful completion of at least one approach and landing in Category II or better conditions, prior to commencing Category III operations.
 - (2) For runways with irregular pre-threshold terrain or other foreseeable or known deficiencies, each aeroplane type/on-board equipment/runway combination must be verified by operations in Category I or better conditions, prior to commencing Category II or III operations.
 - (3) If an operator has different variants of the same type of aircraft utilising the same basic flight control and display systems, or different basic flight control and display systems on the same type of aircraft, the operator must show that the various variants have satisfactory performance, but the operator need not conduct a full operational demonstration for each variant/runway combination.
 - (4) Operators using the same aeroplane type/variant and on-board equipment combination and procedures may take credit from each other's experience and records in complying with this paragraph.

3.3.3 Records

During the evaluation programme the following information must be maintained by the applicant for the aircraft with respect to each approach and made available to the CAA upon request;

- (a) Each deficiency in airborne instruments and equipment that prevented the initiation of an approach.
- (b) The reasons for discontinuing an approach, including the altitude above the runway at which it was discontinued.
- (c) Speed control at the 100 foot decision height if auto throttles are used.
- (d) Trim condition of the aircraft upon disconnecting the auto coupler with respect to continuation to flare and landing.
- (e) Position of the aircraft at the middle marker and at the decision height indicated both on a diagram of the basic ILS display and a diagram of the runway extended to the middle marker. Estimated touchdown point must be indicated on the runway diagram.
- (f) Compatibility of flight director with the auto coupler, if applicable.
- (g) Quality of overall system performance.



4. CERTIFICATION

4.1 Approval

The AWO approval will be issued on Specific Approval Certificate for General Aviation operators, a copy of which must be carried in the aircraft for all flights where AWO may be expected to be conducted.

The AWO approval will be granted by inclusion in the Operations Specifications of the AOC holder.

Note: The limits to be included in the Operations Specifications or LOA are stated in the relevant tables of CAR OPS 1, Subpart E for the specific aeroplane category.

4.2 Certificate of Competency

Once approved and upon request, the CAA will also prepare a Certificate of Competency for the operator to send to foreign states with CAT II/III airports for their approval. No person may conduct a Category II/III approach in a foreign country without the authorisation from the National Aviation Authority of that country and only then in accordance with that Authority.

5. OPERATING PROCEDURES

The commander must satisfy himself that:

- (a) The status of the visual and non-visual facilities is sufficient prior to commencing a Low Visibility Take-Off, Lower than Standard Category I or a Category II;
- (b) Appropriate LVPs are in force according to information received from Air Traffic Services, before commencing a Low Visibility Take-off, Lower than Standard Category I or a Category II; and
- (c) The flight crew members are properly qualified prior to commencing a Low Visibility Take-off in a RVR of less than 150 m (Category A, B and C aeroplanes) or 200 m (Cat D aeroplanes), Lower than Standard Category I or a Category II approach.
- (d) The commander shall satisfy himself that the status of the aeroplane and of the relevant airborne systems is appropriate for the specific operation to be conducted.

6. APPROVAL

The operational approval is issued as an Approval Certificate/Operations Specifications, which must be carried on all flights in the aircraft. The minimums normally included in the approval are;

- | | | | |
|-----|---------------------------|---|--|
| (a) | LVTO | - | not below 125 m RVR (Category A,B & C) |
| | | - | not below 150 m RVR (Category D) |
| (b) | Lower than Standard Cat 1 | - | DH 200ft (all Categories) |
| | | - | RVR 450m (all Categories) |



- (c) CAT II
 - DH 100ft (all Categories)
 - RVR 300m (Category A, B & C)
 - RVR 350m* (Category D)

Note: Category D aeroplanes may be granted RVR 300m if conducting an autoland.*

- (d) CAT IIIA
 - DH < 100ft (all Categories)
 - RVR 200m (all Categories)
- (e) CAT IIIB
 - DH < 100ft or no decision height (all Categories)
 - RVR 75 - 200m (all Categories)
- (f) CAT IIIC
 - not available at present.



This Page Intentionally Left Blank